

**Amaran HC100/HN100**

Function

Specifications

Manual

Specifications:

LED Number	100		Color temperature	5500k ± 200k
LED Angle	45°			
CRI	>95 Ra		Sync speed	>1/200 S
Illumination	50 cm	1020 lux	Power	≤6 W
	100 cm	305 lux		
Supply power voltage	DC 3.6 V-6.7 V		Average life span	>100,000 hours


Compatibility:

AHL-HC100	Canon
AHL-HN100	Nikon

Aputure®		Movie Solution	Amaran HC100/HN100	
Amaran LED Lights	Light Storm	DSLR Field Monitor	Microphones	
EZ Box+ Softbox kit(Grid)	Light Storm COB120t	V-screen VS-2 FineHD	A.lav ez	
Easy Frost	Light Storm LS 1c	V-screen VS-1 FineHD	A.Lav lavalier	
Amaran AL-528	Light Storm LS 1	V-Screen VS-2	V-Mic D2	
Amaran AL-H198/H198C	Light Storm 1/2w	V-Screen VS-3	V-Mic D1	
Amaran HR672		V-Screen VS-1		
Amaran AL-H160				
Amaran HC100/HN100				
Amaran AL-528C				
Amaran AL-528S				
Follow focus				
DEC LensRegain				
DEC Lens Adapter				
V-Wheel				


Aputure Products Guide 2015 Download

Welcome to aputure! Here is our latest products guide in PDF format. We are offering the best movie solutions, lighting systems and camera accessories to our clients. It contains products categories include Led video lights, flash triggers, lens adapters and more. Learn about Aputure products, get the latest downloads now!



Aputure
Like Page 10K likes

Be the first of your friends to like this



[About](#) | [Partnership Program](#) | [Contact](#) | [Sitemap](#)

Copyright © 2008-2022 Aputure Imaging Industries Co. Ltd. All rights reserved.